

CAMPIOCOLOR

M6



Apparecchio da laboratorio per tintura, universalmente impiegabile per fibre tessili, naturali, sintetiche o miste sia in pezza, fiocco o matassa con procedimento per esaurimento.

Laboratory unit universally employed to dye textile natural, synthetic fibres or blends, piece, flock or skein till the complete absorption of the colour.

CARATTERISTICHE GENERALI:

1. Apparecchio modulare con n. 6 posti di tintura.
2. Bicchieri in acciaio inox a scelta da 100-200-300-400-500 o 600 cc.
3. Ottimo isolamento del bagnomaria di riscaldamento che riduce drasticamente le perdite termiche.
4. La temperatura del bagnomaria viene mantenuta costante in tutti i punti della vasca di riscaldamento grazie alla circolazione del liquido riscaldante.
5. Regolazione della temperatura (max 98° C.) controllata da un programmatore a microprocessore avente una capacità massima di 20 programmi memorizzabili, a 20 passi cad.
6. Termostato elettronico di sicurezza.
7. Raffreddamento automatico indiretto ad acqua con elettrovalvola.
8. Fornita di un tipo di portamateriale a scelta per pezza, fiocco e matassa.
9. Movimento del tessuto con traslazione verticale.
10. Apparecchio costruito in acciaio inox.
11. Dimensioni in mm.: lunghezza 850-profondità 500-altezza 660.
Alimentazione elettrica: 3 x 400 V. Trifase + N. - 50 Hz.

GENERAL CHARACTERISTICS:

1. Modular unit with 6 dyeing places.
2. Stainless steel beakers by choice, capacity 100-200-300-400-500 or 600 cc.
3. Very good isolation of the heating bain marie which drastically reduces thermic losses.
4. The temperature of the bain marie is maintained constant in the bath thanks to the circulation of the heating liquid.
5. Temperature regulation (max. 98° C.) by means of a versatile microprocessor programmer capacity of memory 20 programmes max., with 20 steps each one.
6. Electronic safety thermostat.
7. Indirect automatic cooling with water by means of electro-valve.
8. Supplied with sample holder, on requirement for pieces, flock or hank.
9. Vertical movement of the fabric.
10. Unit made of stainless steel.
11. Dimensions in mm.: Length 850 - Depth 500 - Height 660.
Electric alimentention: 3 x 400 V. Three-phases + N. - 50 Hz.

L'immagine e la descrizione del presente volantino sono da ritenersi puramente indicative e non vincolanti. Gavazzi S.r.l. si riserva la facoltà di apportare in qualsiasi momento eventuali modifiche al prodotto.

Photograph and description of present leaflet have to be considered as purely indicative and not binding. Gavazzi S.r.l. reserves the right to introduce at any time possible changes to the product.

GAVAZZI srl
Unipersonale

via Alpini, 100 - 24059 Urgnano (BG) - ITALY
tel. (0039) 035.897697 - fax (0039) 035.890516
www.gavazzilab.it - e-mail: info@gavazzilab.it

